

Description

IS60 is an effective product, used for the preservation of metals, leaving a clear, invisible film, easy to remove when its work is done. Used extensively in the plastic moulding industry it is non-staining and an efficient de-watering agent.

Benefits & Features

- Removes water from the surface of all metal
- Clean, invisible film
- Non-staining
- Thin coating – easily removed or moulded off
- Up to 2 years inside storage protection

Directions for Use

Clean surface to be treated. Shake can well before use and spray a light film from 20–30 cm, ensuring surface is completely covered. Leave to dry to invisible film before closing mould. Clean off with IS/25 Mould Cleaner.

Technical Data

Appearance:	Golden, viscous liquid leaving a waxy film
Odour:	Sweet oily odour
Contents:	Blend of white spirit, naphtha, mineral oils, sarcosine and imidazoline surfactants and hydrocarbon waxes and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	Ambient temperature
Specific Gravity:	0.740
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.