TECHNICAL DATA SHEET



TYGRIS GLOSS BLACK PAINT P302

Description

Premium quality paints. Acrylic-based top-coat paints and for a professional finish on most substrates with exceptional ease of use, resulting in a high quality appearance, with 2 nozzles for unique spray patterns.

Benefits and Features

- Acrylic formulation for greater flexibility
- Gives excellent adhesion
- Compatible with most materials
- Can be applied over previously painted surfaces
- Wear and scratch resistant
- High opacity
- Lead Free
- Excellent UV stability non-fading, lasting finish
- Easily identifiable with colour coded artwork

How to Use

Ensure surface is clean, dry and free from grease. For uneven surfaces, those requiring a complete colour change or extra protection, apply primer first. Prepare with a light sanding for good adhesion. Switch between nozzles for desired spray pattern. Shake can vigorously for 2 minutes and spray a number of light coats with a sweeping action from 25-30cm. Paint should be touch- dry and ready for over-coating in 15 minutes and fully dry within 24 hours. After use, invert can and spray to clear nozzle. Coverage 1.5-2m² per can.

Typical Product Analysis

Appearance: **Black Paint**

Typical paint aroma (Organic Solvents) Odour: Blend of pigments, viscosity modifiers, Contents: stabilisers, solvents and hydrocarbon

propellants

Below 50°C Storage: Flash Point: <0°C

Packaging

12 x 400ml cans

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

