

## Description

Effective cleaning of brakes, clutches and other surfaces. This powerful cleaning fluid is used to remove oil, grease, dirt and dust from brakes and clutches, aiding in the elimination of brake squeal and clutch slip caused by glazing and contamination. Can be used on many other surfaces as a powerful cleaning agent.

## Benefits & Features

- Colourless – non-staining
- Fast evaporating solvents
- Effective against grease, brake fluid, brake and clutch dust
- Can be used to remove tar spots from some surfaces
- Eliminates brake squeal and clutch slip

## Directions for Use

Spray liberally on surface to be cleaned. Wipe off with an absorbent cloth. Test brake operation after cleaning if applicable. May affect some painted surfaces – test on an inconspicuous area first. Avoid spraying on hot surfaces or near naked flames. Always dispose of contaminated materials in a sealable container to avoid fire risk.

**Not suitable for use on plastic or rubber components.**

## Technical Data

|                    |  |
|--------------------|--|
| Appearance:        | Colourless, volatile, free flowing liquid  |
| Odour:             | Solvent  |
| Contents:          | Blend of solvents and hydrocarbon propellants  |
| Flash Point:       | <0°C   |
| Solubility:        | Insoluble in water   |
| Temperature Range: | Designed for use at ambient temperatures   |
| Specific Gravity:  | 0.705 - 0.720  |
| Flammability:      | Extremely Flammable  |
| Health & Safety:   | Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> ) |
| Storage:           | Below 50°C   |
| Pack Size:         | 12 x 400ml aerosols  |

## Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

