TECHNICAL DATA SHEET



SILICONE GREASE **R230**

Description

Clear, moisture resistant silicone based grease. A clear, waterproof, silicone based grease, effective for the insulation of electrical contacts against arcing, sealing components from moisture, preserving rubber and seals from degradation and for assistance in parts assembly.

Benefits & Features

- · Effective moisture resistance
- · Clear non-staining formulation
- Good electrical insulating properties
- · Protects rubber seals from degradation
- Excellent lubrication properties
- Non-melting formulation

Directions for Use

Consult the safety data sheet prior to use. Shake can well before use. Ensure area to be sprayed is clear from dirt, grime and moisture. Wipe away excessive amounts. This Aerosol should be stored out of direct sunlight and below 50°C.

Technical Data

Appearance: Clear frothy liquid, dries to clear, greasy

film

Odour: Slightly sweet solvent

Contents: Blend of silicone oil, viscosity modifier,

naphtha and butane/propane propellant

Flash Point: <0°C

Solubility: Soluble in water Temperature Range: -20°C to 150°C

Relative Density: 0.84

Flammability: Extremely Flammable

Health & Safety: Consult Safety Data Sheet (available at

tygrisindustrial.com)

Storage: Below 50°C

Pack Size: 12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

