

#### Description

A specially developed multi-purpose lithium complex grease for lubricating all anti-friction and plain bearings for use in industrial and automotive applications. The grease has shown exceptional performance providing extended lubrication intervals over a wide operating temperature range.

#### Benefits & Features

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile multi purpose grease
- Good mechanical stability extends lubrication intervals

#### Directions for Use

Apply by grease gun, manually or by centralised pumping system capable of conveying NLGI 2 greases.

#### Technical Data

Appearance:	Smooth red grease
NLGI Classification:	2
Base Oil:	Solvent refined mineral
Base Oil Viscosity:	oil 100cSt
Thickener:	Lithium complex
Worked Penetration:	220-250
Welding Load:	310kg
Copper Corrosion:	1a
Water Washout:	3.5% @ 38°C
Drop Point:	>180°
Temperature Range:	-10 to 130°C
Oil Separation:	3.1%
Timken OK Load:	29kg
Pack Sizes:	24 x 400g cartridges



#### Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.