

# 7510/14 Safe-Torque Speed Tool set for carbide inserts, 14 pieces

Series 7500 Kraffform Safe-Torque Speed Torque Screwdrivers -



**EAN:** 4013288230683  
**Part number:** 05075840001  
**Article number:** 7510/14

**Size:** 175x125x61 mm  
**Weight:** 436 g  
**Country of origin:** CZ  
**Customs tariff number:** 82079030


- Particularly suitable for bolting carbide inserts
- Torque screwdriver with quick torque adjustment
- Easy and quick torque setting
- Fixed position (Torque Lock) for unlimited tightening and loosening moments
- Secure slip-over torque function for clockwise/anti-clockwise torque-control
- Quick and easy setting of the selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm)
- For bits with 1/4" external hexagon drive, also suitable for socket wrench inserts via adapter
- Tools with Hex-Plus profile prevent premature rounding of hexagonal socket screws

14-piece tool set. For professional screwdriving/professional fine adjustment AND for torque-controlled screwdriving. Secure slip-over torque mechanism with quick clockwise/counterclockwise setting and five selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm) and one fixed position (Torque Lock) for unlimited loosening and tightening moments. Quick-release holder for high robustness; suitable for bits with 1/4" external hexagon drive. 14 tough bits (25 mm length) for TORX PLUS®, TORX® and hexagonal socket screws. The tool set is particularly suitable for bolting carbide inserts. The Safe-Torque Speed 7510 torque wrench with its five selectable torque values recommended by leading carbide tool manufacturers ensures a reliable torque-controlled screw connection of replaceable carbide inserts.

## Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraffform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7510\\_14.html](https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7510_14.html)

Wera - 7510/14  
05075840001 - 4013288230683



**For bolting carbide inserts**



Torque screwdriver with quick torque adjustment



The tool set is particularly suitable for bolting carbide inserts. The Safe-Torque Speed 7510 torque wrench with its five selectable torque values recommended by leading carbide tool manufacturers ensures a reliable torque-controlled screw connection of replaceable carbide inserts.

**Five selectable tightening torques**



Five selectable tightening torques (1.0; 1.5; 2.0; 2.5; 3.0 Nm) and one fixed position (Torque Lock) for unlimited tightening and loosening moments.

**Simple setting**



Easy setting of the selectable tightening torques.

**Excess-load signal**




Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

**Storage and transport**



Storage and transport in a robust and compact textile roll bag, so the tool is always close at hand.

**Flexible thanks to hook and loop fastener strips**



The textile box features a fleece zone at the back. Using the provided self-adhesive hook and loop fastener strips, the textile box can be attached to the Wera 2go components. Or to the wall, shelf or workshop trolley.

**Web link**

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraffform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7510\\_14.html](https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7510_14.html)

Wera - 7510/14  
05075840001 - 4013288230683

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## 7510/14 Safe-Torque Speed Tool set for carbide inserts, 14 pieces

Series 7500 Kraffform Safe-Torque Speed Torque Screwdrivers -





Set contents:

### 7510 Kraffform Safe-Torque Speed Torque screwdriver, 1-3 Nm, 1/4" x 1.0 Nm x 1.5 Nm x 2.0 Nm x 2.5 Nm x 3.0 Nm x 147.5 mm



05075810001 1x 1/4" x 1.0 Nm x 1.5 Nm x 2.0 Nm x 2.5 Nm x 3.0 Nm x 147.5 mm





### 867/1 IP TORX PLUS® bits, 7 IP x 25 mm

	05066276001	1x 7 IP x 25 mm
	05066278001	1x 8 IP x 25 mm
	05066279001	1x 9 IP x 25 mm
	05066280001	1x 10 IP x 25 mm
	05066282001	1x 15 IP x 25 mm

### 867/1 TORX® bits, TX 7 x 25 mm

	05066494001	1x TX 7 x 25 mm
	05066495001	1x TX 8 x 25 mm
	05066496001	1x TX 9 x 25 mm
	05066485001	1x TX 10 x 25 mm
	05066486001	1x TX 15 x 25 mm

### 840/1 Z bits, 2 x 25 mm

	05056305001	1x 2 x 25 mm
	05056310001	1x 2.5 x 25 mm
	05056315001	1x 3 x 25 mm

#### Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraffform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7510\\_14.html](https://products.wera.de/en/torque_tools_series_7500_kraffform_safe-torque_speed_torque_screwdrivers_null_7510_14.html)

Wera - 7510/14  
05075840001 - 4013288230683

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)